

## Optimization of the spray pyrolysis technique for ceramic powders synthesis

© Alexander S. Zhukov,<sup>1</sup> Vladimir A. Arkhipov,<sup>2,3,\*+</sup> Sergey S. Bondarchuk,<sup>3</sup> and Tatiana V. Zhukova<sup>1</sup>

<sup>1</sup>Physical Technical Faculty. Tomsk State University. Lenin St., 36. Tomsk, 634050. Russia.

Phone: +7 (3822) 231-42-30. E-mail: zhuk\_77@mail.ru

<sup>2</sup>Research Institute of Applied Mathematics and Mechanics of Tomsk State University.

Lenin St., 36. Tomsk, 634050. Russia. Phone: +7 (3822) 52-96-56. E-mail: zharova@niipmm.tsu.ru

<sup>3</sup>Institute for Problems of Chemical and Energetic Technologies Siberian Branch of RAS. Biysk.

Socialistichiskay St., 1. Biysk, 659322. Russia. Phone: +7 (3854) 30-14-43. E-mail: ipcet@mail.ru

\*Supervising author; +Corresponding author

**Keyword:** *spray pyrolysis technique, solution of metal salt, diffusion, heat transfer evaporation, crystallization, metal oxides, particles morphology.*

### Abstract

A physics and mathematics model of the operating processes in the plasma-chemical reactor for ceramic powders synthesis is presented. The analysis of numerical results has allowed to conduct the estimation of reactor operating conditions and initial solution (precursor) characteristics on the morphology of the formed particles.