

## Changing of chemical composition of lube fraction in solvent refining and dewaxing processes

© Sergey A. Antonov,<sup>1+\*</sup> Natalia N. Tomina,<sup>1\*</sup> Andrey A. Pimerzin,<sup>1</sup> Yulia V. Eremina,<sup>1</sup>  
Yury N. Horoshev,<sup>2</sup> Marina V. Babinceva,<sup>3</sup> and Irina I. Zanozina<sup>3</sup>

<sup>1</sup> Department of Chemical Technology of Oil and Gas Refining, Samara State Technical University,  
Molodogvardejskaja St., 244. Samara, 443100. Russia.

Phone: +7 (846) 242-35-80. E-mail: antonov\_sa@bk.ru

<sup>2</sup> Novokuibyshevsk Oils and Additives Plant. Proizvodstvennaja St., 2. Novokuibyshevsk, 446207.  
Samara Region. Russia. Phone: +7 (84635) 33-1-26. E-mail: KhoroshevYuN@nzmp.rosneft.ru

<sup>3</sup> Department of Physical-Chemical Methods of Research. Middle-Volga Research Institute of Oil Refining.  
Novokuibyshevsk, 446200. Glavpochta. Samara Region. Russia. Phone: +7 (84635) 35-9-81.  
E-mail: zanozinaii@mail.ru

\*Supervising author; †Corresponding author

**Keywords:** structure-group composition, aromatic hydrocarbons, solvent refining, dewaxing.

### Abstract

The 360-450 °C lube fraction was derived from the mixture of sulfur oils. It was involved into solvent refining process by three steps counter-flow method and subsequent dewaxing. The chemical composition and physical-chemical properties of lube fraction was investigated during the refining process.