

Supercritical [SC]-CO₂ extraction glycyrrhizic acid from licorice roots

© Bahodir T. Muhammadiev, Karim Kh. Gafurov, and Shokhista U. Mirzaeva*[†]

Department of Information and Communication Process Control Systems. Bukhara Engineering Technology Institute. K. Murtazoyev St., 15. Bukhara, 200100. Republic of Uzbekistan.

Phone: +998 914-017-905. E-mail: shohista.m@rambler.ru

*Supervising author; [†]Corresponding author

Keywords: extraction, supercritical CO₂, glycyrrhizic acid, licorice root, temperature, pressure.

Abstract

This study used a supercritical (SK) of CO₂-extraction to extract glycyrrhizic acid (GA) from the licorice root. To do this, define the conditions (preliminary experiments) of the extraction process, namely, the temperature, pressure and fluid flow SK (CO₂). Given that this process is multifactorial, the method RSM-response surface methodology and CCRD-central composite rotatable design used to determine the optimum operating conditions of the process. The effectiveness of the established SC-CO₂ extraction conditions, expressed GA content in the extracts as compared with a yield of GA produced by the conventional extraction method, when applied SC-CO₂ modified polar co-solvent (ethanol).

In describing the GA yield predictions using appropriately combined with RSM CCRD, we found that the yield of GA mainly depends on the pressure and quantity of SC-CO₂ used for extraction. It turned out that there is a significant relationship for the linear and quadratic terms of the relationship between the output of the GA and these parameters. Noticeable interaction between the three process parameters (pressure, SC-CO₂ temperature and flow rate) was observed.

Licorice root is subjected to moisture-heat pre-treatment. Cooked thereafter pitch used as a raw material for the extraction of GA by SC-CO₂ extraction. Initial studies for a wide spectrum of SC-CO₂ density value (780-890 kg/m³) indicates that it is possible to set optimum operating conditions for the GA separation.

According to RSM-analysis of the optimal process conditions: 14.6 KPa, 33.5 °C and 21.88 g CO₂/g.d.m. CO₂ consumption for the extraction of GA from licorice using SC-CO₂. SC-CO₂ density calculated for the optimum pressure and temperature equal to 885 kg/m³, which was found as a result of a preliminary analysis of the correlation between the output of the GA and CO₂ density. The maximum yield of GA is equal to 0.158 g of 1 g of dried material (about 15% of extract) with SC-CO₂ density equal 863 kg/m³.

Preliminary tests performed at condition resulting in SK-CO₂ density ranging from 780 to 890 kg/m³ indicated that at some pressure, temperature as well as consumption of supercritical fluids the optimal working conditions for glycyrrhizic acid isolation could be determined. For this purpose the following range of working conditions of SK-CO₂ were tested by using Central Composite Rotatable Design (CCRD) and Response Surface Methodology (RSM): pressure from 16 to 34 KPa, temperature from 20 °C to 40 °C and consumption of SK-CO₂ from 10 to 26 gCO₂/gd.m. The results of this investigation indicated that maximum yield G.A. 158 mg from 1 g materials on dry basis (about 15% of total extract) at 14.6 KPa, 33.5 °C and 21.88 gCO₂/gd.m. could be obtained.

References

- [1] K.H.Gafurov, Sh.U. Mirzaeva, B.T. Muhammadiev. Supercritical CO₂ extraction kinetics with a co-solvent of fat-containing materials from melon seeds. *Butlerov Communications*. **2016**. Vol.48. No.11. P.35-39. ROI: jbc-02/16-48-11-35
- [2] B.T. Muhammadiev, K.H. Gafurov, Sh.U. Mirzaeva, M.F. Sharipova. lipid extraction speed of melon seeds with supercritical CO₂ co-solvent. *Kazakhstans Chemical Magazine, Almaty*. **2016**. P.169-176.
- [3] Sh.U. Mirzaeva, B.T. Muhammadiev, K.H. Gafurov, K.E. Ruzieva, V.N. Ahmedov. Modeling different modes of extraction solvent system ethanol + CO₂ Scientist of the XXI century, publishing house "Colloquium" LLC. *Yoshkar-Ola*. **2017**. No.1-3. P.44-48.
- [4] A. Bogdanovich et. Al. Supercritical carbon dioxide extraction of *Trigonellagoenum-graccum* L. Seed`s: process optimization using response surface methodology. *The jour. Super. Fluids.07*. **2016**. P.44-50.

- [5] A.F. Safarov, K.H. Gafurov. The use of liquid carbon dioxide as a solvent for extracts from plants (review). *Bukhara*. **2014**. P.117.
- [6] B.T. Muhammadiyev, K.H. Gafurov. Perspectives of extraction with CO₂. The development of science and technology. *Beaty*. **2015**. No.4. P.153-159.
- [7] S.M. Ghoreishi et. al. Response surface optimization of essential oil and diosgenin extraction from *Inbutisterrestis* via supercritical fluid technology. *Chem. Ing. Technol.* **2012**. Vol.35 (1). P.133-141.
- [8] B. Kaufmann et. al. Influence of plant extraction processes. *Phytohem. Anal.* **18**. **2007**. P.70-76.
- [9] P. Kraulis, P.R. Venskutionis. Optimization of supercritical carbon dioxide extraction of amaranth seeds by response surface methodology and characterization of extracts is plated from different plant cultivars. *Jour. Supercrit. Fluids*. **2013**. Vol.73. P.178.
- [10] H. Matlab, Z. Sadat, A. Hezave. Training cascade-formed back propagation network modeling of spearmint oil extraction in a packed bea using SC-CO₂. *Jour. Supercrit. Fluids*. **2013**. Vol.73. P.108.