

## Study of electret and dielectric properties of epoxiamine polymer materials

© Ekaterina N. Mochalova,<sup>1\*</sup> Ivan V. Lounev,<sup>2</sup> Mansur F. Galikhanov,<sup>1</sup>

Ildar A. Gabrakhmanov,<sup>1</sup> Roza R. Fatikhova,<sup>2</sup> Yury A. Gusev,<sup>2</sup> and Rustam Ya. Deberdeev<sup>1</sup>

<sup>1</sup> Department of Processing Technology of Plastics and Composite Materials. Institute of Polymers.

Kazan National Research Technological University. K. Marx St., 68. Kazan, 420015. Tatarstan Republic.

Russia. Phone: +7 (843) 231-43-88. E-mail: emmochalova@mail.ru

<sup>2</sup> Department of Radiophysics. Institute of Physics. Kazan (Volga) Federal University. Kremlevskaya St., 18. Kazan, 420008. Tatarstan Republic. Russia. Phone: +7 (843) 233-71-72. E-mail: lounev75@mail.ru

\*Supervising author; <sup>†</sup>Corresponding author

**Keywords:** epoxide oligomer, diethylene triamine, thermoelectret, dielectric permittivity.

### Abstract

Electret and dielectric properties of polymer materials based on epoxide oligomer DER-311 and toughener of diethylene triamine obtained with different ratio of components and under different conditions of curing are studied. Its advantage is a possibility of comparatively easy change (upgrade) of epoxy polymer materials physical and mechanical properties via structural changes in epoxy resin polymer third-dimensional. Epoxy polymer curing process were proceeded in a special cell to unite with polarization in a constant electrical field. It is shown that maximal values of thermoelectret electret characteristic goes with stoichiometric toughener content in the volume of epoxide polymer and increasing of curing temperature. During the first days after charging polymer electrets surface potential, effective surface charge density and intensity of electrostatic field decrease rapidly, then they stabilize on a certain level. For thermoelectrets based on epoxy resin with 10% toughener at 60<sup>th</sup> day after charging surface potential  $V_e = 0.661$  kV, effective surface charge density  $\sigma_{eff} = 0.362 \mu C/m^2$  and electrostatic field intensity of the electret  $E = 45.7$  kV/m. Dielectric measurements were made in frequency range from 1 Hz to 1 MHz via dielectric spectrometer Novocontrol BDS Concept-80 with automatic temperature control using cryosystem QUATRO. Dielectric experimental data handling were made using WinFit program package. For quantity analysis of dielectric spectra Havriliak-Negami distribution were used. Via dielectric spectroscopy method is proved that dipole groups orientation of epoxide polymer macromolecules fixed by third-dimensional grid and are carriers of thermoelectret charge occurs under polymer transfer into electret state. Electret state of polymer matrix is characterized by a free state of epoxiamine macromolecules.

### References

- [1] G.M. Sessler, R. Gerhard-Multhaupt (editors). Electrets. Third edition in two volumes. *California, USA: Laplacian Press, Morgan Hill. 1998/1999.* 472/360 p.
- [2] V.N. Kestelman, L.S. Pinchuk, V.A. Goldade. Electrets in Engineering: Fundamentals and Applications. *Boston-Dordrecht-London: Kluwer Acad. Publ. 2000.* 281p.
- [3] K. Ren, Y. Liu, H.F. Hofmann, Q.M. Zhang. Epoxy 1-3 Composite for Energy-Harvesting Application Single Crystal PMN-PT. *IEEE Transactions on Ultrasonics, Ferroelectrics, and Frequency Control. 2006.* Vol.53. No.3. P.631-1496.
- [4] A.V. Sharipova, O.D. Fominyh, M.Yu. Balakina. Supramolecular organization of chromophores in nonlinear optical epoxyamine oligomers with dendritic chromophore-containing fragments. *Butlerov Communications. 2013.* Vol.35. No.7. P.10-18. ROI: jbc-02/13-35-7-10
- [5] V.N. Studentsov, E.A. Skudaev, R.V. Levin. The curing and application of materials based on blends of three different thermosetting resins. *International Polymer Science and Technology. 2014.* Vol.41. No.11. P.11-14.
- [6] G.N. Nazmieva, T.A. Vakhonina, N.V. Ivanova, A.Sh. Mukhtarov, N.N. Smirnov, A.V. Yakimansky, M.Yu. Balakina, O.G. Sinyashin. Testing of the ways for synthesis of new nonlinear optical epoxy-based polymers with azochromophores in the side chain. *Eur. Polym. J. 2015.* Vol.63. P.207-216.
- [7] E.N. Mochalova, N.A. Limarenko, M.F. Galikhanov, R.Ya. Deberdeev. Effect of the Amount of Curing Agent, Curing Temperature, and Polarization on Physicomechanical Characteristics of Epoxyamine

- Adhesive Compositions Based on DER-331 Oligomer. *Polymer Science, Series D*. **2016**. Vol.9. No.4.  
P.396-401.
- [8] V.I. Irzhak, S.M. Mezhikovskii. Structural aspects of polymer network formation upon curing of oligomer systems. *Russian Chemical Reviews*. **2009**. Vol.78. No.2. P.165-194.
- [9] K. Mazur. More data about dielectric and electret properties of poly(methyl methacrylate). *J. Phys. D: Appl. Phys.* **1997**. Vol.30. P.1383-1398.
- [10] M. Grima, E. Laredo, A. Bello, N. Suarez. Correlation between dipolar TSDC and AC dielectric spectroscopy at the PVDF glass transition. *J. of Polym. Sci.: Part B: Polym. Phys.* **1997**. Vol.35. P.2483-2493.
- [11] P. Marin-Franch, D.L. Tunnicliffe, D.K. Das-Gupta. Dielectric properties and spatial distribution of polarization of ceramic + polymer composite sensors. *Mat. Res. Innovat.* **2001**. No.4. P.334-339.
- [12] M. Olszowy. Dielectric and pyroelectric properties of the composites of ferroelectric ceramic and poly(vinyl chloride). *Cond. Matt. Phys.* **2003**. Vol.6. No.2(34). P.307-313.
- [13] H. Smaoui, M. Arouse, H. Guermazi, S. Agnel, A. Toureille. Study of relaxations in epoxy polymer by thermally stimulated depcurrent (TSDC) and dielectric relaxation spectroscopy (DRS). *Journal of Alloys and Compounds*. **2010**. Vol.489. P.429-436.
- [14] M.F. Galikhanov, Yu.A. Gusev, I.V. Lounev, M.A. Vasilyeva, R.Ya. Deberdeev. Dielectric properties of polyolefin corona electrets. *Vestn. Kazansk. Tekhnol. Univ.* **2015**. Vol.18. No.3. P.40-43. (russian)
- [15] A.A. Guzhova, I.V. Lounev, M.A. Vasilyeva, E.M. Galikhanov, M.F. Galikhanov, Yu.A. Gusev. Dielectric properties of polylactic acid corona electrets. *Vestn. Kazansk. Tekhnol. Univ.* **2015**. Vol.18. No.20. P.29-32. (russian)
- [16] E. Galikhanov, I. Lounev, A. Guzhova, Yu. Gusev, M. Galikhanov, M. Vasilyeva. Study of polylactic acid electret by dielectric spectroscopy. *AIP Conference Proceedings*. **2016**. Vol.1722. 290002.
- [17] A.A. Guzhova, I.V. Lounev, M.F. Galikhanov, Yu.A. Gusev, M.A. Vasilyeva, E.M. Galikhanov. Study of electret state in polylactic acid with nanosized filler by dielectric spectroscopy. *AIP Conference Proceedings*. **2016**. Vol.1748. 020007.
- [18] S. Havriliak, S. Negami. A complex plane analysis of  $\alpha$ -dispersions in some polymer systems. *J. Polymer Sci.-Part C: Polymer Symposia*. **1966**. Vol.14. No.1. P.99-117.
- [19] G.N. Nazmieva, T.A. Vakhonina, S.M. Sharipova, N.V. Ivanova, I.P. Nizameev, M.I. Valitov, N.N. Smirnov, A.V. Yakimanskiy, M.Yu. Balakina. Synthesis and nonlinear optical properties of polyether polyols of azochromophore groups with different structures. *Butlerov Communications*. **2013**. Vol.35. No.7. P.59-67. DOI: jbc-02/13-35-7-59