

Effects of slag basicity and B₂O₃ content on the viscosity of CaO-SiO₂-B₂O₃-25%Al₂O₃-8%MgO oxide system

© Anatoly A. Babenco,^{1,2*} Alena G. Upolovnikova,¹⁺ and Artem N. Smetannikov^{1,2}

¹Laboratory of Pyrometallurgy of Non-Ferrous Metals. Institute of Metallurgy of the UB of the RAS. Amundsen St., 101. Ekaterinburg, 620016. Sverdlovsk Region. Russia.

Phone: +7 (343) 232-90-24. E-mail: upol.ru@mail.ru

²Ural Federal University Named after the First President of Russia B.N. Yeltsin. Mira St., 19. Ekaterinburg, 620002. Sverdlovsk Region. Russia.

* Supervising author; +Corresponding author

Keywords: boron containing slags, basicity, viscosity, experimental planning, composition – viscosity diagrams.

Abstract

A simplex-lattice method of experiment planning that allows obtaining mathematical models describing the dependence of the property on composition as a continuous function was used to study the effect of basicity and B₂O₃ content in slag on the viscosity of the CaO-SiO₂-B₂O₃ oxide system containing 25% Al₂O₃ and 8% MgO. Mathematical models describing the relationship between the temperature of a given viscosity and the composition of the oxide system were constructed using experimental data. Then the set of viscosity isolines was obtained by combining the obtained composition-temperature diagrams of a given viscosity by the isothermal section of the composition-viscosity diagram. The generalization of the results presented in the form of composition-property diagrams allowed to quantify the effect of slag basicity and the B₂O₃ content on the viscosity of the resulting oxide system. The viscosity of slag basicity 2.0-2.5, containing 7-10% B₂O₃ does not exceed 4 Ps at a temperature of 1400 °C. The displacement of slags in the region of increased to 3-5 basicities is accompanied by an increase in the viscosity of slags to 12 Ps while the content of B₂O₃ is reduced to 2-6%. An increase in temperature to 1450 °C leads to a significant decrease in slags viscosity, which in the basicity range 2-3, even at a B₂O₃ content of 4%, does not exceed 4 Ps and increases to 6 Ps in basicity 3-5 and a content of B₂O₃ not more than 3%. The slag viscosity in the basicity range 2-5 varies within 2-4 Ps at a B₂O₃ content of 1-4% at a temperature of 1500 °C. It has been established that slags in the basic 2-5 range containing 1-10% B₂O₃ are characterized at constant concentrations of Al₂O₃ (25%) and MgO (8%) with a high liquid mobility, whose viscosity in the temperature range 1450-1500 °C does not exceed 4-6 Ps. Such slags have, as a rule, high refining properties and can be recommended for the formation on the ladle furnace.

References

- [1] S.M. Chumakov, A.M. Lamukhin, S.D. Zinchenko. The concept of production of low-sulfur steels at OAO Severstal, taking into account the technological aspects. Proceedings of the Sixth Congress of Steel-smelters. Moscow: JSC Chermetinformaton. 2001. P.63-66. (russian)
- [2] S.I. Popel. The theory of metallurgical processes. Moscow: Metallurgiya. 1986. 463p. (russian)
- [3] G.A. Sokolov. Out-of-furnace refining of steel. Moscow: Metallurgiya. 1977. 208p. (russian)
- [4] W. Hongming, Z. Tingwang, Z. Hua. Effect of B₂O₃ on Melting Temperature, Viscosity and Desulfurization Capacity of CaO – based Refining Flux. *ISIJ International*. 2011. Vol. 51. No.5. P.702-708.
- [5] Steel production. Volume 1. Processes of smelting, out-of-furnace processing and continuous casting / Dyudkin D.A., Kisilenko V.V. Moscow: Heat engineer. 2008. 528p. (russian)
- [6] V.I. Kurpas, L.I. Krupman, S.S. Brodsky. Improved technology of out-of-furnace refining of steel. *Sb.nauch.-tekh. statey iz zhurnala «Stal'»*. Moscow: Metallurgiya. 1987. P.61-64. (russian)
- [7] D. Takahashi, M. Kamo, Y. Kurose, H. Nomura. Deep steel desulphurisation technology in ladle furnace at KSC. *Ironmaking and Steelmaking*. 2003. Vol.30. No.2. P.116-119.
- [8] P.K. Iwamasa and R.J. Fruehan. Formation and behaviour of Mn containing oxysulphide inclusions during desulphurisation, deoxidation and alloying. *Metall. Mater. Trans.* B.28. 1997. P.47.
- [9] P. Yan, X. Guo, S. Huang, J. Dyck, M. Guo, B. Blanpain. Desulphurisation of Stainless Steel by Using CaO-Al₂O₃ Based Slags during Secondary Metallurgy. *ISIJ International*. 2013. Vol.53. No.3. P.459-467.

- [10] Gaye H. and Lehmann J. Modeling and prediction of reactions involving metals, slags and fluxes. *VII International Conference on Molten Slags Fluxes and Salts, The South African Institute of Mining and Metallurgy*. **2004**. P.619-624.
- [11] Hui-xiang Yu, Xin-hua Wang, Mao Wang, Wan-jun Wang Desulfurization ability of refining slag with medium basicity. *Int. J. Miner. Metall. Mater.* **2014**. Vol.21. No.12. P.1160-1166.
- [12] A.A. Akberdin, G.M. Kireeva, I.A. Medvedovskaya. Influence of B_2O_3 on the viscosity of slags of the system $CaO-SiO_2-Al_2O_3$. *Izvestiya AN SSSR. Metall.* **1986**. No.3. P.55-56. (russian)
- [13] H. Wang, G. Li, R. Dai. CAS-OB refining slag modification with B_2O_3-CaO and CaF_2-CaO . *Ironmaking and Steelmaking*. **2007**. Vol.4. No.34. P.350-353.
- [14] A.A. Babenko, S.A. Istomin, E.V. Protopopov, A.V. Sychev, V.V. Ryabov. The viscosity of the slag system $CaO-SiO_2-Al_2O_3-MgO-B_2O_3$. *Izvestiya VUZov. Chernaya Metallurgiya*. **2014**. No.2. P.41-43. (russian)
- [15] V.A. Kim, A.A. Akberdin, I.S. Kulikov. The use of lattices simplex charting-type structure - the viscosity. *Izvestiya VUZov. Chernaya Metallurgiya*. **1980**. No.9. P.167-168. (russian)
- [16] V.A. Kim, E.I. Nikolai, A.A. Akberdin, I.S. Kulikov. The planning experiment the study of physical - chemical properties of metallurgical slags: Toolkit. *Alma-Ata: Nauka*. **1989**. 116p.
- [17] A.G. Upolovnikova, and A.A. Babenco. Thermodynamic modeling of boron recovery from boron-containing slag. *Butlerov Communications*. **2016**. Vol.48. No.10. P.114-118. DOI: 10.37952/ROI-jbc-01/16-48-10-114
- [18] A.A. Babenco, L.A. Smirnov, V.I. Zhuchkov, A.V. Sychev, and A.G. Upolovnikova. Using of simplex lattices method for diagramming composition-viscosity of the slag system $CaO-SiO_2-Al_2O_3-MgO-B_2O_3$. *Butlerov Communications*. **2016**. Vol.48. No.11. P.40-44. DOI: 10.37952/ROI-jbc-01/16-48-11-40
- [19] Babenko A.A., Zhuchkov V.I., Smirnov L.A. Etc. Research and development of complex manufacturing techniques of low carbon boron steel with low sulfur content. *Stal'*. **2015**. No.11. P.48-50. (russian)
- [20] A.A. Babenko, L.A. Smirnov, V.I. Zhuchkov, E.N. Selivanov. The development of the technology of deep metal desulphurization and microalloying became boron on the UKP under the slags of the $CaO-SiO_2-Al_2O_3-MgO-B_2O_3$ system. *Sbornik trudov XIII mezhdunarodnogo kongressa staleplavil'shchikov: Moscow-Polevskoy*. **2014**. P.174-177. (russian)