

## The properties of the piperillene-styrene copolymer which are nanopatterned of tetraethoxysilane

© Vladimir Yu. Chukhlanov,<sup>1\*</sup> Oleg G. Selivanov,<sup>2</sup> and Natalia V. Chukhlanova<sup>3</sup>

<sup>1</sup> Department of Chemical Technology; <sup>2</sup> Department of Biology and Ecology; <sup>3</sup> Department of Biology and Ecology. Alexander Grigorievich and Nikolay Grigorievich Stoletovs State University of Vladimir.

Gorkogo St., 87. Vladimir, 600000. Vladimir Region. Russia.

Phone: <sup>1</sup>+7 (4922) 47-99-46; <sup>2</sup>+7 (4922) 47-97-53; <sup>3</sup>+7 (904)030-08-61.

E-mail: <sup>1</sup>chukhlanov11@gmail.com ; <sup>2</sup>selivanov6003@mail.ru ; <sup>3</sup>natalyferre@yandex.ru

\*Supervising author; <sup>+</sup>Corresponding author

**Keywords:** tetraethoxysilane, protective covering, nanopatterning, oligopiperillene–styrene, water repellent, adhesion.

### Abstract

There is has examined the new materials based on copolymer – vinylbenzene and diethenoid monomer – piperillene, which is nanopatterned of ethylic ether of orthosilicic acids – tetraethoxysilane in this work. It is estimated that over injection tetraethoxysilane in composition derive it decomposition to nanoparticles of silicon oxide. Studied of nanostructure of surfaces and influence of composition and nature of the component of polymer compound on physical characteristics. Upon studying of structure of the polymer compound used methods of atomic force microscopy. Water repellent of composition is defined at angle of capillarity of drench. For investigation of adhesive characteristics of obtainable of material used method of breaking of the dial from base. Relative hardness defined with help pendulum instrument M3. Methods of atomic force microscopy it was established presence at surface structure of composition which is modified of tetraethoxysilane, nano-dimensional growths (at the mean one hundred twenty under one square micrometer) with the diameter of two from five nanometers. Herewith changes physical aspects of material: to mount firmness, to growth angle of capillarity of drench. Studied nano-structured composition can find applied appliance. For example, it is using as protective covering with complex of tailored properties, such as high water repellent.

### References

- [1] Arun Anand Prabu, Muthukaruppan Alagar. Arun Mechanical and electrical studies of silicone modified polyurethane-epoxy intercrosslinked networks. *Polymer Journal*. **2004**. Vol.36. No.10. P.848-855.
- [2] V.Yu. Chukhlanov., Selivanov O.G. Dielectric properties of sealing compositions based on epoxy resin modified by polymethylphenylsiloxane on centimetric ultra-high frequencies - radio region. *Glues. Luting compositions. Technologys*. **2015**. No.3. P.6-10. (russian)
- [3] M.L. Kerber, V.M. Vinogradov, G.S. Golovkin. Polymer composite: structure, properties, technology: schoolbook. Eds. A.A. Berlin. *Spb.: Profession*. **2008**. 536p. (russian)
- [4] V.Yu. Chukhlanov, S.S. Kriushenko and N.V. Chukhlanova. Elastic Polyurethane Foams Modified by Tetraethoxysilane. *Theoretical Foundations of Chemical Engineering*. **2015**. Vol.49. No.4. P.518-522. (russian)
- [5] V.Yu. Chukhlanov., Selivanov O.G. Binder for radiotransparent composition material based on epoxy resin modified by alkoxysilane. *Material Engineering*. **2015**. No.6. P.31-36. (russian)
- [6] A.M. Muzafarov. Silicon Polymers. *Berlin: Springer-Verlag Berlin Heidelberg*. **2011**. P.100.
- [7] Kurkin A.I., Kulikov A.V. The influence of nature of polyols based on properties of preferencedialog. *Constructional Material*. **2008**. No.6. P.20-21. (russian)
- [8] V.A. Yamskuy, V.A. Koftuk. The influence of hydrous oligomers on the properties two component polyurethane paints. *Paints and lacquers and it's appliance*. **2008**. No.6. P.14. (russian)
- [9] S.D. Popova etc. Filmogenic properties of piperillene–styrene copolymer SKPS-70M. *Moscow: Paints and lacquers and it's appliance*. **1986**. No.2. (russian)
- [10] V.Yu. Chukhlanov, N.Yu. Nikonova, A.N. Alekseenko. Hydrophobized liquid for concrete and reinforced framing. *Constructional Materials*. **2003**. No.12. P.38-39. (russian)

- [11] B.A. Izmailov, V.A. Vasnev. Modification of surface of the moieties by robust silicone compound. *Plastic Materials*. **2011**. No.6. P.58-61. (russian)
- [12] M.Yu. Dolomatov, M.Yu. Timofeeva. The theory of adhesion of the macromolecular compounds and it's application. *Plastic materials*. **2009**. No.3. P.45-47. (russian)