

## Stability of interpolyelectrolyte complexes of sulfonate-containing aromatic polyamides in aqueous solutions

© Natalia N. Smirnova

Department of Chemistry. Vladimir State University Named after A.G. and N.G. Stoletovs.

Gorkogo St., 87. Vladimir, 600000. Russia. Phone: +7 (9422) 47-98-67. E-mail: smirnovann@list.ru

**Keywords:** interpolymers reactions, interpolyelectrolyte complexes, sulfonate-containing aromatic polyamides, polyamines.

### Abstract

Complexation in aqueous solutions of sulfonate-containing aromatic polyamides and a number of polyamines: polyethyleneimine, poly-*N*-(2-aminoethylacrylamide), poly(2-vinyl-2-imidazoline) and poly-*N,N*-dimethyl-*N,N*-diallylammonium chloride has been studied. It has been shown that as a result of macromolecular reactions, interpolyelectrolyte complexes are formed, stabilized mainly by electrostatic forces. It has been found that in the interpolymer system containing sulfonate-containing aromatic polyamide and poly-*N,N*-dimethyl-*N,N*-diallylammonium chloride, complexes of stoichiometric composition the fractional conversion about 0.9 are formed throughout the investigated pH range. Participation in the complexation reaction of polyethyleneimine, poly-*N*-(2-aminoethylacrylamide) and poly(2-vinyl-2-imidazoline) leads to the formation of interpolyelectrolyte complexes stable in neutral and acid environment, where the complexation tends to complete and the amount of salt bonds in the corresponding complex increases. It has been shown that the process of phase separation in the interpolymer systems containing weak polybase can be adjusted by varying their composition. In the case of complexes of non-stoichiometric composition enriched with polyanion, there is a shift of the pH range associated with phase separation systems in more interpolymer acidic region. Based on the studied interpolyelectrolyte complexes, materials with high strength characteristics were obtained. The tensile strength of the film samples is 65-84 MPa with a relative elongation of 20-65%. It has been shown that synthesized materials are characterized by high regulated hydrophilicity that, in combination with good mechanical properties, allows to consider them as promising for use in hydrophilic pervaporation processes.

### References

- [1] V.V. Volkov, B.V. Mchedlishvili, V.I. Roldugin, S.S. Ivanchev. Membrane in nanotechnology. *Russian nanotechnology*. **2008**. Vol. 3. No.11-12. P.67-100. (russian)
- [2] Comprehensive membrane science and engineering. Ed. by E. Drioli, L. Giorno. *Amsterdam: Elsevier*. **2010**. Vol.2. 490p.
- [3] Membrane separations chemical, pharmaceutical, food, and biotechnological applications: handbook. Ed. by A.K. Pabby, S.H. Rizvi, A.M. Sastre. *New York: CRC Press*. **2015**. 845p.
- [4] G. Banfalvi. Permeability of biological membranes. *Switzerland: Springer Int. Publ*. **2016**. 273p.
- [5] V.A. Kabanov. Polyelectrolyte complexes in solution and in condensed phase. *Russ. Chem. Rev.* **2005**. Vol.74. No.1. P.5-24. (russian)
- [6] A.E. Thünemann, M. Müller, H. Dautzenberg, J.-F. Joanny, H. Löwen. Polyelectrolyte complexes. *Adv. Polym. Sci.* **2004**. Vol.166. P.113-171.
- [7] Polyelectrolytes. Ed. by P.M. Visakh, O. Bayraktar, G.A. Picó. *Switzerland: Springer Int. Publ*. **2014**. 388p.
- [8] A. Ettori, E. Gaudichet-Maurin, P. Aimar, Ch. Causserand. Mass transfer properties of chlorinated aromatic polyamide reverse osmosis membranes. *Separ. Purif. Technol.* **2012**. Vol.101. P.60-67.
- [9] Y. Jin, S. Liang, Z. Wu, Zh. Cai, N. Zhao. Simulating the growth process of aromatic polyamide layer by monomer concentration controlling method. *Appl. Surf. Sci.* **2014**. Vol.314. P.286-291.
- [10] Ch. Wang, B. Shen, Y. Zhou, Ch. Xu, W. Chen, X. Zhao, J. Li. Sulfonated aromatic polyamides containing nitrile groups as proton exchange fuel cell membranes. *Int. J. Hydrog. Energ.* **2015**. Vol.40. P.6422-6429.

- [11] Yu.A. Fedotov, N.N. Smirnova. Aromatic polyamides with ionogenic groups: synthesis, properties and applications. *Plastic*. **2008**. No.8. P.18-21. (russian)
- [12] P. Rao, B. Smitha, S. Sridhar, A. Krishnoieh. Preparation and performance of poly(vinylalcohol)/polyethyleneimine blend membranes for the dehydration of 1,4-dioxane by pervaporation6 comparison with glutaraldehyde cross-linked membranes. *Separ. Purif. Technol.* **2006**. Vol.48. P.244-254. (russian)
- [13] N.N. Smirnova, V.I. Volkov. Interpolyelectrolyte complexation as a tool for controlling the mechanical, sorption and diffusion properties of film materials. *Rus. J. Appl. Chem.* **2015**. Vol.88. No.3. P.475-483.