

Analysis of permanganous oxidity of tap water and of the efficiency of its household treatment

© Galina B. Senitskaya,*⁺ and Alla V. Khalikova

Samara State Transport University. Department of Natural Sciences.

Svobody St., 2 B. Samara, 443066. Russia. Phone: +7 (906) 340-46-29. E-mail: Senitskaya@mail.ru.

*Supervising author; ⁺Corresponding author

Keywords: tap water, open source water, permanganate oxidation, purification, iron content.

Abstract

In the article results of researches of tap water quality of Samara central water supply system are shown. As the most common purity criterion, permanganate oxidizability was chosen. A solution of potassium permanganate in an acidic medium oxidizes both organic and inorganic substances in the water. Based on the results of titrimetric analysis, the indicator of chemical oxygen consumption was calculated, which, according to the standards, should not exceed 5 mg/l for drinking water. Samples of tap water taken in different districts of Samara were investigated. As a comparison, the permanganate oxidizability of the open source water in the Samara region was measured. It is shown that permanganate oxidizability in the same region can fluctuate within wide limits, the difference being 25%. It was found that none of the samples examined meets the sanitary requirements for drinking water. An analysis of samples of tap water on the content of iron ions was made and their absence was shown, which made it possible to conclude that there was no influence of the corrosion processes of water pipes and equipment on the permanganate oxidation capacity. The efficiency of water purification by household filters has also been studied. As the research objects, the pitcher filters of the Barrier and Aquafor companies, occupying the main market segment, and the automatic multi-stage water purification system EkoMaster, widely distributed in organizations and offices, were selected. It is shown that only the "Barrier" filter slightly reduces the permanganate oxidizability, without achieving regulatory values. The "Aquaphor" filter and the "EcoMaster" purifier increase the value of permanganate oxidizability of tap water, which indicates a low resource of these water purification systems.

References

- [1] *SanPiN 2.1.4.1074-01* "Drinking water. Hygienic requirements for water quality of centralized drinking water supply systems. Quality control". (russian)
- [2] *SanPiN 2.1.4.1175-02* «Hygienic requirements for water quality of non-centralized water supply. Sanitary Protection of Sources». (russian)
- [3] *GOST R 55684-2013* The drinking water. Methods for determining permanganate oxidizability.
- [4] *GOST 4011-72* Drinking water. Methods for measuring the mass concentration of total iron. (russian)
- [5] O.D. Dyakova, D.S. Koshlina, A.V. Khalikova, G.B. Senitskaya. Determination of iron (III) ions in water by photometric method. Materials of the regional scientific and practical conference "Education, science, transport in the 21st century: experience, prospects, innovations. *Samara-Orenburg*. 2010. P.127-128. (russian)