### **Short Communication**

 Reference Object Identifier – ROI: jbc-02/18-56-11-160
 Subsection: Chemical Technology.

 Publication is available for discussion in the framework of the on-line Internet conference "Chemical basis for the rational use of renewable natural resources".
 http://butlerov.com/natural\_resources/

Submitted on November19, 2018.

# Perspectives of low-temperature plasma application in chemical and oil refining industry

## © Vladimir B. Pavlov,<sup>1</sup>\* EkaterinaA. Shulaeva,<sup>2+</sup> and Elena A. Kralkina<sup>3</sup>

 <sup>1</sup> Department "Automated Technology and Information Systems"; <sup>2</sup> Department "Automated Technology and Information Systems". Branch of the Ufa State Petroleum Technological University in Sterlitamak. Oktyabrya Ave., 2. Sterlitamak, 453118 Bashkortostan Republic. Russia.
 Phone: <sup>1)</sup> +7 (3473) 24-25-12, <sup>2)</sup> +7 (3473) 24-25-12. E-mail: <sup>1)</sup> vb\_pavlov@mail.ru ; <sup>2)</sup> eshulaeva@mail.ru <sup>3</sup>Physical Electronics Department. Faculty of Physics. Lomonosov Moscow State University. Vorobjevy Gory. Moscow, 119991. Russia. Phone: +7 (495) 939-47-73. E-mail: ekralkina@mail.ru

\*Supervising author; <sup>+</sup>Corresponding author

*Keywords:* regeneration of catalysts, low-temperature plasma, ion beam, the ion energy, the current of the ion beam, surface modification, regeneration of catalysts.

### Abstract

The paper describes the prospects of low-temperature plasma application in the chemical and oil refining industry. The methods of increasing the efficiency of catalysts are considered. For this purpose, it is proposed to change the properties of the surface layer of the catalyst without changing its internal structure. This can be achieved by the usage of ion-beam and plasma technologies. Existing technologies of surface plasma modification can be implemented at different pressures: ion-beam technologies of materials processing at high vacuum, technologies of materials processing at low and atmospheric pressure. The choice of one or another method of plasma modification of the catalyst surface depends on the necessary characteristics that should posses the resultant material.

Plasma treatment of structural materials used in the production of chemical equipment allows to achieve the required parameters of the thin surface layer. Depending on the task, it can be hardening, deposition of anti-corrosion, antibacterial layers, etc.

### References

- [1] A.M. Kutepov, A.G. Zakharov, A. I. Maksimov. Vacuum-plasma and plasma-solution modification of polymeric materials. *Moscow: Science*. **2004**. 496p. (russian)
- [2] L.G. Bugaenko, M.G. Kuzmin, L.S. Polak. High energy chemistry. *Moscow: Chemistry.* **1988**. 368p. (russian)
- [3] A.F. Alexandrov, K.V. Vavilin, E.A. Kralkina, V.B. Pavlov. Promising plasma and ion-beam nanotechnologies. Plasma sources. Devices. *Scientific-practical conference "Fundamental and applied aspects of innovative projects of MSU faculty of Physics"*, 18-19 November **2009**. Moscow. P.25-26. (russian)
- [4] V.B. Pavlov, E.A. Shulaeva. Plasma activation of the catalyst surface. *Scientific-practical conference "Modern technologies in education and industry: from theory to practice". Ufa: Publishing House "Oil and Gas business».* **2018**. P.146-148. (russian)
- [5] G.K. Boreskov. Heterogeneous catalysis. *Moscow: Science*. 1988. 304p. (russian)
- [6] V.P. Sukhanov. Catalytic processes in oil refining. *Moscow: Chemistry.* 1973. 416p. (russian)
- [7] Catalyst Technology. Under the editorship of I.P. Mukhlenov. *Leningrad: Chemistry.* **1979**. 324p. (russian)
- [8] B.S. Danilin. Vacuum processes and equipment for microelectronics. *Moscow: Machinery*. **1987**. 72p. (russian)
- [9] E.A. Baranov, A.O. Zamchiy, S.Ya. Khmel. Synthesis of oriented arrays of microchannels from silicon oxide nanowires by gas-jet chemical deposition with electron-beam plasma activation. *Technical physics letters*. 2013. Vol.39. No.22. P.88-94. (russian)

PERSPECTIVESOF LOW-TEMPERATURE PLASMA APPLICATION IN CHEMICAL AND OIL...

- [10] A.A. Chizhevsky, I.S. Abdullin, V.S. Zheltukhin. Production of catalysts by plasma modification or treatment of the carrier. Bulletin of technological University. 2015. Vol.18. No.14. P.159-162. (russian)
- [11] K.V. Vavilin, E.A. Kralkina, V.B. Pavlov at al. Method of modification of surface properties of materials and device. Russian patent No.2371258. (russian)
- G.I. Lashchenko. Plasma hardening and coating. *Kiev: Ecotechnology*. 2003. 65p. [12]
- [13] A.F. Alexandrov, G.E. Bugrov, E.A. Kralkina, V.B. Pavlov at al. Comparative analysis of different surface modifications methods. Contr. Papers of IV Intern. Conf. "Plasma Physics and Plasma Technology". 2003. Vol.2. P.530-533.
- [14] A.F. Alexandrov, E.A. Kralkina, V.B. Pavlov at al. The frequency effect on atmospheric pressure RF discharge surface modification. Journal of Ceramic Processing Research. 2007. Vol.8. No.1. P.64-69.
- [15] A.F. Alexandrov, E.A. Kralkina, V.B. Pavlov at al. RF Discharge at Atmospheric Pressure and the Effects on Material Surface Property. Contr. Papers of Intern. Sympos. on pulsed Power and Plasma Application. 2004. P.197-202.