

Sucrose absorption by products of hydration of the Portland cement

© Evgeny A. Shoshin,^{1*+} and Valeria V. Strokhova²

¹ "Construction Materials and Technologies" Department. Yuri Gagarin State Technical University of Saratov. Politekhnikeskaya St., 77. Saratov, 410054. Russia.

Phone: +7 (8452) 99-86-03. E-mail: ssstu_office@sstu.ru

² Department of Materials Science and Technology of Materials. V.G. Shukhov Belgorod State Technological University. Kostyukov St., 46. Belgorod, 308012. Russia.

Phone: +7 (4722) 54-90-41. E-mail: vvstrokhova@gmail.com

*Supervising author; +Corresponding author

Keywords: portland cement, hydration products, structure, sucrose, absorption.

Abstract

Portland cement hydration products that are formed during its intensified hydration (grinding of cement-cement slurry) under conditions of high values of water-cement ratio and the presence of significant amounts (more than 1 % by mass) of modifying carbohydrate (sucrose) were studied. The structure and phase composition of the modified cement intensified products were determined by X-ray phase analysis and electron diffraction from the selected site. The latter are a mixture of weakly crystallized and crystalline (ettringite) phases. The elemental analysis of hydrated silicate phases revealed the identity of the control and modified samples according to the content of SiO₂ and CaO, while the content of structural water was increased by 12% in the modified sample. The sucrose content in the liquid phase of water-cement suspensions subjected to milling was evaluated. Using a spectrophotometric method using an anthron (9,10-dihydro-9-oxo-anthracene) reagent, it was found that the products of intensified cement hydration have a high ability to absorb sucrose. Over the entire range of the studied concentrations of sucrose (2.5-16.6%), the degree of its absorption by the solid phase exceeds 98%. The threshold concentration of modifying sucrose was determined, the excess of which leads to a sharp increase in the equilibrium concentration of sucrose in the liquid phase of water-cement suspensions. The study of cement hydration products modified with various amounts of sucrose by the method of differential thermal analysis in atmospheric conditions revealed a discrepancy between the increase in mass loss of the samples and the amount of sucrose added to modify the sample. For every additional 3% sucrose introduced into the composition of the water-cement slurry for the intensified hydration of cement, the increase in mass loss of samples of modified hydration products at temperatures above 200 was 1.7-2.0%. The latter suggests the formation of compounds including Saccharose – Products of cement hydration.

References

- [1] N.L. Thomas, J.D. Birchall. The mechanism of retardation of setting of OPC by sugars. *Proceedings of the British Ceramic Society*. **1984**. No.35. P.305-315.
- [2] Khan Bazid, Baradan Bulent. The effect of sugar on setting-time of various types of cements. *Science vision quarterly*. **2002**. Vol.8. No.1. P.71-78.
- [3] F.L. Gleckel. Physico-chemical bases of application of additives for mineral binders. *Tashkent: Fan*. **1975**. 198p.
- [4] Zhang Linghong, J.J. Lionel, Raymond Catalan, J. Balec, Andrew C. Larsen, Hassan Haji Esmaeili, Stephen D. Kinrade. Effects of saccharide set retarders on the hydration of ordinary portlandcement and pure tricalcium silicate. *Journal of the American Ceramic Society*. **2010**. Vol.93. No.1. P.279-287.
- [5] Maria C. Garci Juenger, Hamlin M. Jennings. New insights into the effects of sugar on the hydration and microstructure of cement pastes. *Cement and Concrete Research*. **2002**. Vol.32. No.3. P.393-399.
- [6] B.J. Smitha, A. Rawala, G.P. Funkhouser, L.R. Roberts, V. Gupta, J.N. Israelachvilia, B.F. Chmelka. Origins of saccharide-dependent hydration at aluminate, silicate, and aluminosilicate surfaces. *Proceedings of the National Academy of Sciences of the United States of America*. **2011**. Vol.108. No.22. P.8949-8954.

- [7] J.F. Young. A review of the mechanisms of set-retardation in Portland cement pastes containing organic admixtures. *Cement and Concrete Research*. **1972**. No.2(4). P.415-433.
- [8] K. Luke, G. Luke. Effect of Sucrose on Retardation of Portland Cement. *Advances in cement research*. **2000**. No.12. P.9-18.
- [9] M. Bishop, A.R. Barron. Cement Hydration Inhibition with Sucrose, Tartaric Acid, and Lignosulfonate: Analytical and Spectroscopic Study. *Industrial and engineering chemistry research*. **2006**. No.45. P.7042-7049.
- [10] V.K. Peterson, M.C.G. Juenger. Hydration of Tricalcium Silicate: Effects of CaCl_2 and Sucrose on Reaction Kinetics and Product Formation. *Chemistry of Materials*. **2006**. No.18. P.5798-5804.
- [11] N. Pannetier, A. Khoukh, J. François. Physico-Chemical Study of Sucrose and Calcium Ions Interactions in Alkaline Aqueous Solutions. *Macromolecular Symposia*. **2001**. Vol.166. P.203-208.
- [12] S.J. Angyal. Complexes of Metal Cations with Carbohydrates in Solution. *Advances In Carbohydrate Chemistry and Biochemistry*. **1989**. Vol.47. P.1-43.
- [13] C. Nalet, A. Nonat. Ionic complexation and adsorption of small organic molecules on calcium silicate hydrate: Relation with their retarding effect on the hydration of C_3S . *Cement and Concrete Research*. **2016**. Vol.89. P.97-108.
- [14] R. Susilorini. The Use of Sugar, Sucrose and Sugar Cane Liquid Mix as Sugar Based Admixture for Mortar. *Prosiding Seminar Nasional Teknik Sipil VI "Pengembangan Infrastruktur dalam Menunjang Pembangunan Ekonomi Nasional"*. **2009**. Vol.27. P.251-258.
- [15] O.V. Tarakanov. Cement materials with carbohydrate additives. *Penza: PSACA*. **2003**. 166p. (russian)
- [16] E.A. Shoshin, A.A. Shirokov. Investigation of the electrokinetic potential of carbohydrate-modified cement pastes at the initial stage of hydration. *Bulletin of BSTU named after V.G. Shukhov*. **2015**. No.5. P.235-240. (russian)
- [17] C. Nalet, A. Nonat. Impacts of hexitols on the hydration of a tricalcium aluminate-calcium sulfate mixture. *Cement and Concrete Research*. **2016**. Vol.89. P.177-186.
- [18] G.P. Smitha, L.R. Funkhouser, Roberts V. Gupta, B.F. Chmelka. Reactions and Surface Interactions of Saccharides in Cement Slurries. *Langmuir: the ACS journal of surfaces and colloids*. **2012**. Vol.28. P.14202-14217.
- [19] J. Plank, Z. Dai, N. Zouaoui. Novel hybrid materials obtained by intercalation of organic comb polymers into Ca–Al–LDH. *Journal of Physics and Chemistry of Solids*. **2008**. Vol.69. P.1048-1051.
- [20] E.A. Shoshin, A.V. Polyakov, N.N. Bylinkina, A.M. Burov. Microscopic examination of the products of thermal dehydration of modified cement hydrosilicates. *Bulletin of BSTU named after V.G. Shukhov*. **2016**. No.1. P.18-25. (russian)
- [21] E.A. Shoshin, Yu.G. Ivashchenko, A.V. Polyakov, V.M. Bulanov. Research of cement hydrosilicates modified by isomeric disaccharides by the method of differential thermal analysis. *News of the Kazan State University of Architecture and Engineering (Kazan)*. **2017**. No.1(39). P.244-249. (russian)
- [22] Lu Zeng, Ligang Yang, Shuping Wang, Kai Yang. Synthesis and characterization of different crystalline calcium silicate hydrate: application for the removal of aflatoxin B1 from aqueous solution. *Journal of Nanomaterials*. **2014**. P.1-10.
- [23] Hiroyoshi Matsuyama, Francis J. Young. Intercalation of polymers in calcium silicate hydrate: a new synthetic approach to biocomposites? *Chemistry of Materials*. **1999**. No.11. P.16-19.
- [24] J. Plank, D. Zhimin, H. Keller, F. Hössle, W. Seidl. Fundamental mechanisms for polycarboxylate intercalation into C_3A hydrate phases and the role of sulfate present in cement. *Cement and Concrete Research*. **2010**. No.40. P.45-57.
- [25] J. Plank, D. Zhimin, P.R. Andres. Preparation and characterization of new Ca–Al–polycarboxylate layered double hydroxides. *Materials Letters*. **2006**. Vol.60. P.3614-3617.
- [26] Helene Viallis-Terrisse, Andr'e Nonat, Jean-Claude Petit. Zeta-potential study of calcium silicate hydrates interacting with alkaline cations. *Journal of Colloid and Interface Science*. **2001**. No.244. P.58-65.
- [27] E.A. Shoshin, Yu.G. Ivashchenko. Study of the composition of cement hydrosilicates modified with isomeric disaccharides. *Regional architecture and construction*. **2016**. No.3(28). P.50-54. (russian)
- [28] V.S. Ramachandran. The use of differential thermal analysis in the chemistry of cements. Translated from English, edited by V.B. Ratinov. *Moscow: Stroiizdat*. **1977**. 408p. (russian)
- [29] E.Yu. Lebedeva, A.A. Kobyakova, N.T. Usova, O.V. Kazmina. Synthesis of tobermorite adsorbent for water purification. *Bulletin of the Tomsk Polytechnic University*. **2014**. Vol.324. No.3. P.137-141. (russian)

- [30] Properties of organic compounds. Book of reference. Edited by A.A. Potekhin. *Leningrad: Chemistry*. **1984**. 520p. (russian)
- [31] N.K. Kochetkov et al. Carbohydrates chemistry. *Moscow: Chemistry*. **1966**. 674p. (russian)
- [32] Y.E. Young. Effect of organic compounds on the Interconversion of calcium Aluminate Hydrate. Hydratation of the Tricalcium Aluminate. *J. of the American Ceramic Society*. **1970**. No.53. P.65-69.
- [33] Y.E. Young. Reaction mechanism of Organic Admixtures with Hydrating Cement Compounds. *Transportation Research Record*. **1976**. No.564. P.1-9.